


GSA 錶接頭

- 液壓設備與壓力錶更易結合。
- 公接頭端可連接泵浦或油壓缸；母接頭端可連接油管或快速接頭；第三接口端即為壓力錶接頭端。

Gauge Accessories

- ※ Easy mounting of pressure gauge into hydraulic system.
- ※ Male end screw into pump or cylinder port, female end accepts hose or coupler, third port is for gauge connection.



型號 Model Number	錶接頭 Gauge port C(NPTF)	公接頭 Male end D(NPTF)	母接頭 Female end E(NPTF)	外型尺寸 Dimensions(mm)					
				A	B	C	D	E	F
GSA-1	1/2	3/8	3/8	71	31	1/2NPTF	3/8NPTF	3/8NPTF	32
GSA-2	1/2	3/8	3/8	155	35	1/2NPTF	3/8NPTF	3/8NPTF	32
GSA-3	1/4	3/8	3/8	133	48	1/4NPTF	3/8NPTF	3/8NPTF	32
GSA-4	1/2	1/4	3/8	111	35	1/2NPTF	1/4NPTF	3/8NPTF	32
GSA-3H	1/4	3/8	3/8	90	28	1/4NPTF	3/8NPTF	3/8NPTF	26H
GSA-452	1/4	1/4	1/4	50	—	1/4NPTF	1/4NPTF	1/4NPTF	38
GSA-453	1/4	3/8	3/8	50	—	1/4NPTF	3/8NPTF	3/8NPTF	38

SO 液壓油 Hydraulic Oil

GF10 高抗磨耗性液壓油 (低溫地區適用)。

- 主要成份為高品質基礎油混合精選添加劑而成。
- 成份包含液壓油 HL 型式，完全符合DIN51525或51524標準規格。
- 內含抗氧化、防銹、抗磨損及抗泡沫添加劑。
- 能降低低荷載泵浦在連續使用中，因空氣泡沫產生黏稠所造成的損害。
- 主要適用於液壓油控制及動力傳送系統，同時適用於若干機械之循環或油浴系統。

AW22/ 32/ 46/ 68/ 100/ 150 特級液壓油

- 含特殊添加劑，防止油質氧化，減低金屬磨損及泡沫形成，增加液壓油壽命及保護機件。
- 品質優異之高黏度指數泛用型液壓油，含抗氧化、抗磨損、防銹、消泡等添加劑，防止氧化及酸性物質造成的傷害。
- 極易與水分離，能保持循環系統油路清潔，延長機械使用壽命。
- 適用各種工業用油壓機械、射出成型機、大型油壓沖床等中高油壓系統使用。



High wear-resisting Hydraulic oil (Lower temperature area use) GF10

- ※ Main ingredients is composed by high quality basic oil and additive.
- ※ Include HL hydraulic oil (fit in with DIN51525 or 51524 standard.)
- ※ Include additive which can resisting combustion, rust and wear.
- ※ It also reduce low load pump damage as continuous using which become sticky to result air foam.
- ※ Main application as hydraulic control and/or power transit system and machine.

High grade hydraulic oil AW22/ 32/ 46/ 68/ 100/ 150

- ※ Include special additive that prevent combustion, air foam and increase oil life and protect machine.
- ※ High sticky which used in most application. Additive which can resisting combustion, rust and wear.
- ※ Easy separate oil and water that can increase machine life.
- ※ Use in all application such as industry hydraulic machine, injection machine and mid/ high pressure large hydraulic presses machine.

型號 Model No.	SOW22-4L SOW22-5L	SOW32-4L SOW32-5L	SOW46-4L SOW46-5L	SOW68-4L SOW68-5L
類別 ISO	22	32	46	68
比重 Gravity, SP.GR g/ml	0.868	0.872	0.874	0.879
黏度 40°C Viscosity SUS	22.2	32.1	46.7	68.9
黏度 100°C Viscosity SUS	4.4	5.5	6.9	9.0
黏度指數 Viscosity Index	107	107	103	105
閃火點 Flash Point.°C	200	205	216	221
流動點 Pour Point.°C	-26	-22	-24	-26

型號 Model No.	SOGF10-4L SOGF10-5L
類別 ISO 黏度級數 H-LP	10
比重 Gravity, SP.GR 15°C g/ml	0.855
黏度 0°C Viscosity SUS	50
黏度 40°C Viscosity SUS	10
黏度 100°C Viscosity SUS	2.8
黏度指數 Viscosity Index	98
閃火點 Flash Point.°C	160
流動點 Pour Point.°C	-39